

6 W 6.5" ceiling loudspeaker EN 54, metal



Part-No.: 582408

With its flat forms, the type DL-E. 06-165/T-EN 54-24 is optically a good fit for the ceilings for which they were designed. The 6.5" broadband loudspeaker chassis, which is impregnated against humidity, distinguishes itself by way of its high degree of effectiveness. Typically, the 6 W, 3 W, or 1.5 W power setting can be selected. The spring latch (3 pieces) guarantees an uncomplicated and quick mounting onto the ceiling. In the standard version, a protective cover made out of a synthetic material is mounted to the back side of the loudspeaker, but a fire dome certified according to the EN 54 Part 24 standard is optionally available as well. If the loudspeaker is also meant to be used in accordance with BS 5839-8, it is possible to order the optional thermal fuse and a ceramic terminal, and to mount them (also certified in accordance with EN 54-24).

Rated Power	6 W
Transformer power taps	6/3/1.5 W
Sensitivity EN 54-24, 1 W / 1 m	97,8 dB
Sensitivity EN 54-24, max 1 m	105,3 dB
Transmission range	300 Hz ... 19300 Hz
Ambient temperature	-10 °C ... 55 °C
Color	white, similar to RAL 9016
Weight	approx. 0.76 kg
Cut-out size	(Ø min.) 165 mm
Dimensions	Ø: 200 mm D: 72 mm

Accessories:

Optional:
582408.FD Fire dome (FE 165.1) for ceiling loudspeaker Part No. 582408, 582408.
SAFE