

## 15 W horn loudspeaker EN 54, ABS



### Part-No.: 582479

The horn loudspeaker offers a high sound pressure and long-lasting weather resistance, ideal for use in industrial projects. The IP 66 high protection class guarantees operational safety even under the most difficult conditions. The loudspeaker is also equipped with a ceramic terminal block and a thermal fuse for increased safety. The shock-resistant ABS enclosure according to UL94V0 ensures long-lasting stability. A U-shaped non-corrosive universal bracket is enclosed for flexible mounting. The cable connection is done without need for an additional junction box. The flexible power adjustment can be easily done with the rotary switch on the back side of the loudspeaker. The loudspeaker is also suitable for outdoors use. The loudspeaker complies with standard BS 5859 Part 8, and is certified in accordance with EN 54 Part 24.

Rated Power	15 W
Sensitivity EN 54-24, 1 W / 1 m	105 dB
Sensitivity EN 54-24, max 1 m	117 dB
Transmission range	300 Hz ... 16000 Hz
Ambient temperature	-25 °C ... 55 °C
Storage temperature	-40 °C ... 70 °C
Material	ABS
Color	light grey, similar to RAL 7035
Weight	approx. 2,05 kg
Dimensions	Ø: 213 mm D: 265 mm